



DT-363

Features

- AC / DC Current measurement
- Max. Resolution 10mA
- Display: 4.000 counts, LCD Display with backlight
- AC True RMS
- Data Hold
- Zero Function
- Auto Power Off
- Low battery indication
- Peak Current
- 1,2" (30mm) Jaw opening

The 360 series clamp meters offer all the features you need to fit the way you work. The small bodies and jaws fit perfectly in your hand and are specially designed for using in the tight places. Meter controls are positioned so that current measurements can be done with one hand. The measured result is easily read from the large backlit display. A handy Display Hold keeps measurements on the display.

Technical data

Function	Max Range	Basic Accuracy
Voltage DC	600V	$\pm(0,8\%+2d)$
Voltage AC	600V	$\pm(1,0\%+10d)$
Current DC	400A	$\pm(2,5\%+5d)$
Current AC	400A	$\pm(2,5\%+8d)$
Resistance	40M Ω	$\pm(1,5\%+2d)$
Temperature	1000°C/ 1832°F	$\pm(3,0\%+5^{\circ}\text{C})$
Capacitance	40mF	$\pm(3,0\%+5d)$
Frequency	10MHz	$\pm(1,5\%+2d)$
Continuity check	Buzzer sounds at 50 Ω	
Diode test	Test current 0,3mA	
Size(HxWxD)	197mm x 70mm x 40mm	
Weight	183g	

Delivery

Clamp Meter DT-363, Test Leads, Gift Box with Carrying Case, Temperature Probe, 9V Battery, User Manual (Eng),



CEM Instruments (Germany) GmbH
Hermann-Köhl-Str. 7
28199 Bremen, Deutschland
Email: info@cem-instruments.de, Tel. +49 (0)4219601-370
Web: www.cem-instruments.de

CEM INSTRUMENTS HEADQUATER & FACTORY
19th Building, 5th Region, Baiwangxin Industry Park,
Songbai Road, Baimang, Xili, Nanshan, Shenzhen,
China, 518108

Web: <http://www.cem-instruments.com>
Tel: +86-755-27353188, Fax: +86-755-27653699