

LEAKAGE CLAMP METER

KPS-PF10



- Current leakage clamp with $\varnothing 31$ mm jaw
- 2000 counts
- Three manually selected scales: 2mA / 20mA / 60A
- Retention of readings
- Auto power off
- Low battery indication
- CAT. III 600V according to EN 61010



KPS-PF10

LEAKAGE CLAMP METER

General	
Power Supply	2 × 1.5V AAA Batteries
Product Size	176 mm × 59 mm × 28 mm
Product Weight	150g
Certificate	RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	2000
Jaw Opening	Φ31mm/1.2"
Auto Power Off	✓
Data Hold	✓
Low Battery Display	✓

Specs	Range	Resolution	Accuracy
AC Current	2 mA	0.001 mA	± (2.0% + 10 digits)
	20 mA	0.01 mA	± (2.0% + 8 digits)
	60A (<50A)	0.1A	± (2.0% + 5 digits)
	60A (>50A)	0.1A	± (3.0% + 5 digits)



www.kps-intl.com

KPS-PF10

LEAKAGE CLAMP METER

Product Code Information

SKU	KPSPA440CBINT
EAN code	8435394747231
UPC code	810053670217
Pcs/export carton	20



EMEA
MGL Euman, S.L.
cs.emea@mgl-intl.com
Tel: +34 985-08-18-70

CANADA & USA
MGL America, Inc.
cs.na@mgl-intl.com
Tel: +1 833 533-5899

MEXICO & LATAM
MGL LATAM S.A DE CV
cs.latam@mgl-intl.com
Tel: +1 833-533-5899